

# MID 15~25KTL3-X

- Max. efficiency 98.75%
- Dual MPP trackers
- Supports export control
- Touch key and OLED display
- Type II SPD on AC and DC side



P O W E R  
- I N G O  
T O M O -  
R R O W O

**GROWATT**

[www.ginverter.com](http://www.ginverter.com)

Datasheet	MID 15KTL3-X	MID 17KTL3-X	MID 20KTL3-X	MID 22KTL3-X	MID 25KTL3-X
<b>Input data (DC)</b>					
Max. recommended PV power (for module STC)	22500W	25500W	30000W	33000W	37500W
Max. DC voltage	1100V				
Start Voltage	250V				
Nominal voltage	580V				
MPPT voltage range	160V-1000V				
No. of MPP trackers	2				
No. of PV strings per MPP tracker	2	2	2	2	2/3
Max. input current per MPPT tracker*	27A	27A	27A	27A	27A/40,5A
Max. short circuit current per MPPT	33,8A	33,8A	33,8A	33,8A	33,8A/50,7A
<b>Output data (AC)</b>					
Rated AC output power	15000W	17000W	20000W	22000W	25000W
Max. AC apparent power	16600VA	18800VA	22000VA	24400VA	27700VA
Nominal AC voltage(range*)	220V/380V, 230V/400V (340-440V)				
AC grid frequency;(range*)	50/60 Hz (45-55Hz/55-65 Hz)				
Max. output current	24,2A	27,4A	31,9A	35,5A	40,2A
Adjustable power factor	0.8leading...0.8lagging				
THDi	<3%				
AC grid connection type	3W+N+PE				
<b>Efficiency</b>					
Max. efficiency	98,75%				
European efficiency	98,6%				
MPPT efficiency	99,9%				
<b>Protection devices</b>					
DC reverse polarity protection	Yes				
DC Switch	Yes				
AC/DC surge protection	TypeII/Type II				
Insulation resistance monitoring	Yes				
AC short-circuit protection	Yes				
Ground fault monitoring	Yes				
Grid monitoring	Yes				
Anti-islanding protection	Yes				
Residual-current monitoring unit	Yes				
String monitoring	Yes				
AFCI protection	Optional				
<b>General data</b>					
Dimensions (W / H / D)	525/395/222mm				
Weight	23kg				
Operating temperature range	-25 °C ... +60 °C				
Self-Consumption (night)	< 1W				
Topology	Transformerless				
Cooling	Smart air cooling				
Protection degree	IP65				
Relative Humidity	0-100%				
Altitude	4000m				
DC connection	H4/MC4(Optional)				
AC connection	Cable gland+OT terminal				
Display	OLED+LED/WIFI+APP				
Interfaces: RS485 / USB / WiFi/ GPRS / RF/ LAN	Yes/Yes /Optional/Optional/Optional/Optional				
Warranty: 5 years / 10 years	Yes /Optional				
CE, VDE0126, Greece, EN50549, C10/C11, UTE C 15-712, IEC62116, IEC61727, IEC 60068, IEC 61683, CEI0-21, N4105, TOR Erzeuger, G98/G99, G100, UNE217001, UNE206007, PO12.2, KSC8565					

\* The AC voltage range and frequency range may vary depending on specific country grid standard. All specifications are subject to change without notice.  
 \* Only the latest version with max. input current 13.5A per string, for details please contact Growatt.